
TECHNICAL DATA SHEET

CÓPIA NÃO
CONTROLADA

Code: 6105
Revision: 00
Date: 07/06

PRODUCT: CERAMIC FIBER MODULE JUMBO HT

Description: Nutec Ibar modules have the highest insulating value achievable in ceramic fiber. Each module is a continuous folded blanket, U-loop and stackbond type all under compression.

Mean Application:

Ceramic Industry

- Low mass kiln cars.
- Continuous and batch kilns.
- Door linings and Glazing, porcelain furnace linings.

Power Generation

- Duct lining.
- Heat recovery steam system.
- Boiler insulation and Stack linings.

Refining and Petrochemical

- Ethylene furnace roof and walls.
- Pyrolysis furnace lining.
- Reformer furnace roof and walls
- Boiler linings.

Steel Industry

- Ladle preheaters and covers.
- Heat treat furnace.
- Soaking pit covers and seals.
- Furnace hot face repairs and heaters and reformer lining.

Others

- Insulation of commercial dryers and ovens.
- Stress relieving insulation.
- Fire protection.

Packaging: Wood pallets.

Identification: Label with product name, dimension, quantity, lot number, fabrication date.

Storage Life: Without limit (if properly stored)

Chemical Analysis

Al ₂ O ₃	SiO ₂	Fe ₂ O ₃	TiO ₂
44-50	50-56	0,1-0,2	0,1-0,2

TECHNICAL DATA SHEET

**CÓPIA NÃO
CONTROLADA**

**Code: 6105
Revision: 00
Date: 07/06**

PRODUCT: CERAMIC FIBER MODULE JUMBO HT

Typical Physical Properties

-Maximum use limit	(°C)	1482
-Continuous use limit	(°C)	1200
-Density	(Kg/m ³)	128; 160 192; 224