

**TECHNICAL DATA SHEET**

**CÓPIA NÃO  
CONTROLADA**

**Code: 6301  
Revision: 01  
Date: 07/06**

**PRODUCT: CF CEMENT 1300**

**Description:** Nutec Ibar ceramic fiber cement is produced by using two high purity adhesives to get thick cream consistency and be used applied by brushing or trowelling.

**Mean Application:**

- Cementing modules onto blocks.
- Mortar for refractory bricks.
- Insulation and protections for metallic surfaces.
- To fill voids and cracks in refractory surface.
- Protection against corrosion and abrasion for fiber linings.

**Packaging:** Plastic drums with 25 Kg.

**Identification:** Label with product name, quantity, lot number, fabrication date.

**Storage Life:** 6 months (if properly stored)

**Chemical Analysis**

Al <sub>2</sub> O <sub>3</sub>	SiO <sub>2</sub>	Fe <sub>2</sub> O <sub>3</sub>
47,5	42,5	1,5

**Technical Specifications**

-Maximum Use Limit .....	(°C)	1300
-Max. Cont. Use Limit .....	(°C)	1200
-Normal Layer Thickness .....	(mm)	0,25-1,0
-Application Rate .....	(m <sup>2</sup> /l)	1,2-2,5
-Linear Shrinkage .....	(%)	
	1200 °C x 24 h	3,1
-Color .....		brown